Eles Makina Page No - 15

Duplex System Slitter Rewinder Machine

Machine Model:

EMS-1300

Machine Name:

SLITTER AND REWINDER MACHINE

- → 1200 mm Material Width.
- → 1300 mm Idler Roller Width
- → One Reel on Air Shaft of Unwinder Area
- → Tottally two servo motors in rewinder area.
- → 400 meter/minute Machine Mechanical Speed,.
- → Magnetic Powder Brake System on Unwinder,
- → Multi Reels on Two Friction Shafts of Rewinder Area
- → Rubber Roller, Chrome Metal Roller in Main Roller which is driven by servo motor,
- → Servo Motor driven friction shafts in one of the each two rewinder sections,
- → Real Working Speed depend on the material quality and other conditions.
- → Safety Chucks (Strong and High Speed Resistant) On Unwinder Units locks the air shaft and turn it.
- → 3 inches (76 mm) Air Shaft (Strong and High Speed Resistant) on Unwinder Unit,
- → 10 pcs. Straight(Razor) Cutting Knives and 5 pcs. Round Cutting Kinves Usage Ability,
- → Edge Trim Waste Vacuum Blowing System,
- → Automatic Edge Control in Unwinder,
- → With Servo Torque Mode, Automatic Tension Control in each of the shafts of Rewinder,
- → With Loadcell Tension Control Mode, Automatic Tension Control in Unwinder,
- → 10 inches Touch Screen Control Unit,





